

SMK

Plaster hose - 10 bar



SPECIFICATIONS

Application Specially designed hose for dry application (e.g. cement, grit) and wet application (e.g. plaster, wet concrete).
Developed for conveying abrasive mediums such as cement, sand, aggregates, gravel, etc.

Feature Very long service life due partly to the use of abrasion resistant rubber in the tube and cover, and partly to increased thickness of the tube - thicker wear layer.
Average wear of the tube 70 mm³ [according to DIN ISO 4649:2021].
Antistatic construction prevents the build-up of static electricity.

Temperature range -35°C / +80°C.

Safety factor 3,15 : 1

Tube NR/BR/SBR, black, abrasion resistant, antistatic, smooth.

Reinforcement Textile wrapped.

Cover SBR, black, resistant to ozone and weather, antistatic, cloth impression.

Marking continuous mylartape, white letters: "SEMPERIT [S] SMK Mörtel/ Plaster PN 10 bar".

Notice Flame resistant cover available on request.

TECHNICAL DETAILS

Article number	Internal-Ø		Wall width	External-Ø	Work. pressure [max.]	Number of inserts	Bending radius [min.]	Weight approx.	Coil length [max.]
	mm	inch	mm	mm	bar		mm	kg/m	m
48451 3202	32.0	1 1/4	10.0	52.0	10	2	350	1.70	20
48451 4080	40.0		8.0	56.0	10	2	400	1.55	40
48451 5010	50.0		10.0	70.0	10	2	500	2.35	40
48451 5002	50.0		10.0	70.0	10	2	500	2.35	20
48451 6010	60.0		10.0	80.0	10	2	600	2.55	40
48451 6002	60.0		10.0	80.0	10	2	600	2.55	20
48451 6510	65.0		10.0	85.0	10	4	650	2.65	40
48451 6502	65.0		10.0	85.0	10	4	650	2.65	20

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage [especially of the cover] or unusual signs of wear and tear. All products must be stored, handled, and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. To always have the latest product and safety information make sure you visit our website [hoses.semperitgroup.com] regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts concluded with us are exclusively subject to our general terms and conditions [available at semperitgroup.com]. Additional important general information about the range, choice and safe use of our products can be found at our website [hoses.semperitgroup.com] and must be followed without exception.

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the state-of-the-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620:2005(E). However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or

individual datasheets are therefore strictly subject to your continuous observance of all specifications and restrictions in our written product information and applicable laws and standards, the specifications regarding resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance, or handling (e.g. squashing, rupturing, stretching, or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Products delivered by us to the USA are manufactured according to IRPM-IP2, unless specified otherwise. All other hoses are manufactured according to EN ISO 1307:2008, unless specified otherwise. Our products are not designated for the sale to the general public and do not fulfill the conditions for "GS-certification", unless stated otherwise in the product datasheet.