

SM200

Concrete pumping wire - 100 bar - EN 12001



SPECIFICATIONS

| Application | Specially developed hose for conveying concrete using concrete pumps. Suitable for conveying highly abrasive media such as concrete, cement and plaster. | | | | | |
|-------------------|---|--|--|--|--|--|
| Feature | Long service life due to abrasion resistant tube. | | | | | |
| | Average wear of the tube 50 mm ³ (according to DIN ISO 4649:2021). | | | | | |
| | Thanks to highly abrasion resistant cover, the hose is also particularly resistant to mechanical stress from the outside. | | | | | |
| | Flexible and easy to handle, with good kink resistance due to a special hose design. Suitable for reverse pumping, for easy cleaning. | | | | | |
| Temperature range | -35°C / +80°C. | | | | | |
| Safety factor | 2:1 | | | | | |
| Tube | NR/BR/SBR, black, abrasion resistant, antistatic, smooth. | | | | | |
| Reinforcement | Steel wrapped. | | | | | |
| Cover | SBR, black, highly abrasion resitant, resistant to ozone and weather, antistatic, cloth impression. | | | | | |
| Marking | continuous mylar tape, red letters: "SEMPERIT [S] SM200 inch/DN CONCRETE PUMPING WP 100 bar 1450 PSI weight incl. concrete max kg/m lbs/ft Made in EU /////" | | | | | |
| Notice | The hose conforms to EN 12001:2011 and ASME B30.27-2014. | | | | | |

TECHNICAL DETAILS

| | | | 0 | 0 | $\textcircled{\textbf{S}}$ | | \square | $\widehat{\square}$ | |
|----------------|------------|------|------------|------------|----------------------------|-------------------|-----------------------|---------------------|--------------------|
| Article number | Internal-Ø | | Wall width | External-Ø | Work. pressure (max.) | Number of inserts | Bending radius (min.) | Weight approx. | Coil length (max.) |
| | mm | inch | mm | mm | bar | | mm | kg/m | m |
| 48398 5195 | 50.8 | 2 | 9.5 | 69.8 | 100 | 4 | 250 | 8.4* | 40 |
| 48398 6511 | 65.0 | | 11.0 | 87.0 | 100 | 4 | 300 | 14.1* | 40 |
| 48398 7511 | 75.0 | | 11.0 | 97.0 | 100 | 4 | 350 | 18.4* | 40 |
| 64398 0213 | 101.6 | 4 | 13.0 | 127.6 | 100 | 4 | 450 | 31.1* | 40 |
| 64398 1214 | 125.0 | | 14.0 | 153.0 | 100 | 4 | 500 | 44.6* | 40 |

*Weight data in the table are values \square of the hose filled with concrete.

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled, and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. To always have the latest product and safety information make sure you visit our website (hoses.semperitgroup.com). Additional important general information about the range, choice and safe use of our products can be found at our website (hoses.semperitgroup.com). Additional important general information about the range, choice and safe use of our products can be found at our website (hoses.semperitgroup.com).

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the state-ofthe-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620:2005[E]. However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to your continuous observance of all specifications and restrictions in our written product information and applicable laws and standards, the specifications regarding resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance, or handling [e.g. squashing, rupturing, stretching, or filling with non-approved media]. Our products must not be used in airplanes or other aerial vehicles under any circumstance. Products delivered by us to the USA are manufactured according to EN ISO 1307:2008, unless specified otherwise. Our products are not designated for the sale to the general public and do not fulfill the conditions for "GS-certification", unless stated otherwise in the product datasheet.