

GOX

Welding/Gas - 20 bar - blue - ISO 3821 (EN 559)



SPECIFICATIONS

Application	A flexible hose for transporting oxygen. For welding and cutting, for arc welding using shielding gas and related processes (Not suitable for LPG, MPS and CNG).				
Standard/Approval	ISO 3821:2019 (formerly EN 559:2003).				
Temperature range	-30°C / +70°C.				
Safety factor	3:1				
Tube	EPDM, black, smooth.				
Reinforcement	Textile spiral.				
Cover	EPDM, blue, ribbed DN >12 smooth.				
Marking	continuous inkjet, black letters: "SEMPERIT (S) GOX ISO 3821 (EN 559) PN 2 MPa (20 bar) II OD -30°C YYYY MADE IN EU /////".				
Notice	Smooth cover available on request. Also available in 40 m lengths.				

TECHNICAL DETAILS

	(0	0	\odot		\square	$\widehat{\square}$	
Article number	Internal-Ø		Wall width	External-Ø	Work. pressure (max.)	Number of inserts	Bending radius (min.)	Weight approx.	Coil length (max.)
	mm	inch	mm	mm	bar		mm	kg/m	m
68402 0435	4.0		3.5	11.0	20	2	40	0.11	50
68402 0535	5.0	3/16	3.5	12.0	20	2	40	0.13	50
68402 0630	6.3		3.0	12.3	20	2	40	0.12	50
68402 0635	6.3	1/4	3.5	13.3	20	2	40	0.15	50
68402 0650	6.3	1/4	5.0	16.3	20	2	40	0.24	50
68402 0830	8.0		3.0	14.0	20	2	40	0.14	50
68402 0835	8.0	5/16	3.5	15.0	20	2	40	0.18	50
68402 0930	9.0	0	3.0	15.0	20	2	45	0.16	50
68402 0935	9.0		3.5	16.0	20	2	45	0.19	50
68402 0955	9.0		5.5	20.0	20	2	45	0.36	50
68402 1030	10.0		3.0	16.0	20	2	50	0.17	50
68402 1035	10.0	3/8	3.5	17.0	20	2	50	0.21	50
68402 1250	12.5	1/2	5.0	22.5	20	2	65	0.40	50
68402 1650	16.0	5/8	5.0	26.0	20	2	80	0.48	50
68402 2055	20.0		5.5	31.0	20	2	100	0.63	50
68402 2550	25.0	1	5.0	35.0	20	2	125	0.70	50

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled, and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. To always have the latest product and safety information make sure you visit our website (hoses.semperitgroup.com) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts concluded with us are exclusively subject to our general terms and conditions (available at semperitgroup.com). Additional important general information about the range, choice and safe use of our products can be found a tour website (hoses.semperitgroup.com) and must be followed without exception.

Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the state-ofthe-art industrial technology and many years of experience and testing; whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7820:2005[E]. However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the catalogue or individual datasheets are therefore strictly subject to your continuous observance of all specifications and restrictions in our written product information and applicable laws and standards, the specifications regarding resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance, or handling [e.g. squashing, rupturing, stretching, or filling with non-approved media]. Our products must not be used in airplanes or other aerial vehicles under any circumstance. Products delivered by us to the USA are manufactured according to RPM-IP2, unless specified otherwise. All other hoses are manufactured according to EN ISO 1307:2008, unless specified otherwise. Our products are not designated for the sale to the general public and do not fulfill the conditions for "GS-certification", unless stated otherwise in the product datasheet.